

International
IR Rectifier

SCHOTTKY RECTIFIER
HIGH EFFICIENCY SERIES

PD-94088B

10YQ045C
JANS1N7045T3
JANTX1N7045T3
JANTXV1N7045T3

10Amp, 45V

Ref: MIL-PRF-19500/735

Major Ratings and Characteristics


Characteristics	1N7045T3	Units
I _{F(AV)}	10	A
V _{RRM}	45	V
I _{FSM} @ t _p = 8.3ms half-sine	110	A
V _F @ 10Apk, T _J = 125°C	0.70	V
T _J , T _{stg} Operating and storage	-65 to 150	°C

Description/Features

The 1N7045T3 Schottky rectifier has been expressly designed to meet the rigorous requirements of high reliability environments. It is packaged in the hermetic isolated TO-257AA package. The device's forward voltage drop and reverse leakage current are optimized for the lowest power loss and the highest circuit efficiency for typical high frequency switching power supplies and resonant power converters. Full MIL-PRF-19500 quality conformance testing is available on source control drawings to TX, TXV and S levels.

- Hermetically Sealed
- Low Forward Voltage Drop
- High Frequency Operation
- Guard Ring for Enhanced Ruggedness and Long Term Reliability
- Lightweight
- Ceramic Eyelets
- ESD Rating: Class 3A per MIL-STD-750, Method 1020

CASE STYLE



Case Outline and Dimensions - TO-257AA

10YQ045C, 1N7045T3

International
IR Rectifier

Voltage Ratings

Part number	1N7045T3		
V_R Max. DC Reverse Voltage (V) (Per Leg)	45		
V_{RWM} Max. Working DC Reverse Voltage (V) (Per Leg)			

Absolute Maximum Ratings

Parameters	Limits	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current See Fig. 5	10	A	50% duty cycle @ $T_C = 119^\circ\text{C}$, square waveform
I_{FSM} Max. Peak One Cycle Non - Repetitive Surge Current	110	A	@ $t_p = 8.3 \text{ ms}$ half-sine

Electrical Specifications

Parameters	Limits	Units	Conditions	
V_{FM} Max. Forward Voltage Drop See Fig. 1①	0.74	V	@ 10A	$T_J = -55^\circ\text{C}$
	0.95	V		
	0.73	V		
	1.02	V	@ 20A	$T_J = 25^\circ\text{C}$
	0.70	V		
	1.10	V	@ 20A	$T_J = 125^\circ\text{C}$
I_{RM} Max. Reverse Leakage Current See Fig. 2①	0.50	mA		
	67	mA	$T_J = 125^\circ\text{C}$	$V_R = \text{rated } V_R$
C_T Max. Junction Capacitance	900	pF	$V_R = 5V_{DC}$ (1MHz, 25°C)	
L_s Typical Series Inductance	9.8	nH	Measured from anode lead to cathode lead 6mm (0.025 in.) from package	

Thermal-Mechanical Specifications

Parameters	Limits	Units	Conditions	
T_J Max.Junction Temperature Range	-65 to 150	°C		
T_{stg} Max. Storage Temperature Range	-65 to 150	°C		
R_{thJC} Max. Thermal Resistance, Junction to Case	2.6	°C/W	DC operation	See Fig. 4
wt Weight(Typical)	3.3	g		
Die Size (Typical)	125X125	mils		
Case Style	TO-257AA			

① Pulse Width < 300μs, Duty Cycle < 2%




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage

10YQ045C, 1N7045T3

International
IR Rectifier




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Max. Allowable Case Temperature Vs.
Average Forward Current

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

IR LEOMINSTER : 205 Crawford St., Leominster, Massachusetts 01453, USA Tel: (978) 534-5776

TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information.
Data and specifications subject to change without notice. 10/2012